

DynaGST/2402G

24 Port 10/100/1000Base-T Unmanaged Gigabit Ethernet Switch with two SFP (Mini) GBIC Slots

PART NUMBER	DESCRIPTION
GEP-33224T-1	24 Port 10/100/1000Base-T Unmanaged Gigabit Ethernet Switch with two SFP (Mini) GBIC Slots

Specifications

Standards:

IEEE802.3 10Base-T 10Mbps, Half/Full Duplex
 IEEE802.3u 100Base-TX, 10/100Mbps, Half/Full Duplex
 IEEE802.3z Gigabit SX/LX 1000Mbps
 IEEE802.3ab Gigabit 1000T 10/100/1000Mbps
 IEEE802.3x Flow control and Backpressure

Connectors:

Copper: Twenty-four RJ-45 ports
 Mini GBIC: Two 3.3V Mini GBIC slots

Protocol:

CSMA/CD

Max Forwarding and Max Filtering Rate:

14,880 pps per Ethernet port
 148,800 pps per Fast Ethernet port
 1,488,000 pps per Gigabit Ethernet port

LED Indicators: Per Port:

Per unit: Power
 Per port: 1000Mbps, Link/Activity, Full duplex/ collision
 Mini GBIC port: Link and Activity

Copper Network Cables:

10Base-T: 2 pairs UTP/STP CAT. 3/5e/6 cable, EIA/TIA 568, 100 Ohm (up to 100m)
 100Base-TX: 2 pairs UTP/STP CAT. 5e/6 cable, EIA/TIA 568, 100 Ohm (up to 100m)
 Gigabit Copper: 4 pairs UTP/STP CAT. 5e/6 cable, EIA/TIA 568, 100Ohm (up to 100m)

MAC Address

4K Mac address table

Memory Buffer

2Mbits

Dimensions:

440 mm x 161 mm x 44.5 mm (L x W x H)
 17.32" x 6.33" x 1.75" (L x W x H)

Storage Temp:

-40°C to 70°C (-40°F to 158°F)

Operational Temp:

0°C to 45°C (32°F to 113°F)

Operational Humidity:

10% to 90% (Non-condensing)

Power Supply:

Internal power supply, AC 100~240VAC, 50/60 Hz

Power Consumption:

60Watts (Maximum)

EMI & Safety:

FCC Class A, CE, UL, CE/EN60950



908 Canada Court
 City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880
 www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.
 Specifications subject to change without notice.