

# SmartGST-900GM

## 8 Port 10/100/1000Base-T Managed Switch with 1000Base-T Port and SFP (Mini) GBIC Slot

| PART NUMBER | DESCRIPTION  |
|-------------|--|
| GEP-66109T  | 8 Port 10/100/1000Base-T Managed Switch<br>with one 1000Base-T Port and SFP (Mini) GBIC Slot |

## Specifications

### Standards:

IEEE802.3 10BASE-T  
IEEE802.3u 100BASE-TX  
IEEE802.3z Gigabit fiber  
IEEE802.3ab 1000Base-T  
IEEE802.3x Flow Control and Back Pressure  
IEEE802.3ad Port Trunk with LACP  
IEEE802.1d Spanning Tree Protocol  
IEEE802.1w Rapid Spanning Tree  
IEEE802.1p Class of Service IEEE802.1q VLAN Tagging  
IEEE 802.1x User Authentication

### Interface:

RS-232 console: Female DB-9, Copper RJ-45: 8 x 10/100/1000T, 1 x 1000T; Mini-GBIC: 1 x Mini-GBIC socket

### Management Interface:

WEB Browser Interface, Simple Network Management Protocol (SNMP), CLI/RMON, and Telnet

### IGMP:

IGMP support to reduce IP multi-cast traffic for the multimedia applications

### VLAN:

Up to 256 static VLAN groups and 2048 dynamic VLAN; the VLAN ID can be assigned from 1 to 4094

### Port Mirroring:

Global system supports 3 mirroring types: "RX, TX, and Both packet"

### Broadcast Storm Filtering:

Only allows a percentage of ports total bandwidth before broadcast traffic is dropped

### Trunking:

Supports 802.3ad port trunking with LACP function.

### Class of Service:

Per system supports high and low queues

### LED Indicators:

1000Base-T: Speed (1000Mbps), Link/Activity,  
Mini-GBIC: Link/Activity (Green)  
Per Unit: Power

### Operational Environment:

0°C to 60°C (32°F to 140°F), 5% to 95% RH

### Dimensions:

217 mm x 140 mm x 43 mm (L x W x H)

### Power Supply:

Internal power 100~240 VAC, 50~60 Hz

### EM and Safety:

FCC Class A, CE Mark, UL, cUL, CE/EN60950

### Management Features:

- Web-based management
- SNMP network management
- DHCP Client, Relay, and Server
- Supports Port based VLAN / 802.1 Q Tag VLAN and double tag VLAN
- Port Trunking with LACP supported
- Port based/Tag based QoS
- Spanning Tree Protocol/Rapid STP
- IP address management security
- SMTP supported (6 mail accounts)
- Port mirror and bandwidth control
- Static MAC Address
- Supports GVRP functions
- Broadcast Storm Filter
- TFTP firmware updatable



908 Canada Court  
City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880  
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.  
Specifications subject to change without notice.