

DualSpeed Converters

10/100Base-TX to 100Base-FX (MM and SM)

PART NUMBER	DESCRIPTION
FEP-5300TF-C	Multi-Mode, Dual SC (2Km)
FEP-5301TF-T	Multi-Mode, Dual ST (2Km)
FEP-5401TF-C	Single Mode, Dual SC (30Km)

Specifications

Standards:

IEEE802.3u 10Base-T/100Base TX /
100Base-FX Fast Ethernet Standards

Interface:

(1) 100Base-TX Shielded RJ-45 Jack

Wavelength:

1310nm

Link Distance:

100 m Max., Category 5e/6 UTP/ScTP –
All Converters
2 km Max., FEP-5300TF-C or FEP-5301TF-T
30 km Max., FEP-5401TF-C

Dip Switch:

ON/OFF for UTP Auto Negotiation,
Fiber Duplexing and Loss Link Forwarding.

Power Supply:

External power adapter 9V DC / 700mA

Operating Temperature:

0°C to 55°C

Operating Humidity:

10% - 80% RH

Enclosure:

Metal

EMI:

FCC, Class A, CE Mark

LED Indicators:

Power, Link/Activity, Receive/Full-Duplex, 100



817 S Lemon Ave. Walnut, CA 91789

Ph: 626-964-7873 Fax: 626-964-7880

www.unicomlink.com email: info@unicomlink.com

Unicom is a trademark of Unicom Electric, Inc. All rights reserved.

Specifications subject to change without notice.