

# Xtend-T/FL (MM)

## 10Base-T/10Base-FL Converter (Multi-Mode)

---

PART NUMBER	DESCRIPTION
ETP-20108	10Base-T/FL Multi-Mode Converter

## Specifications

---

### Interface:

---

RJ-45 Jack for 10Base-T connection  
ST Connector for 10Base-FL Multi-Mode Fiber Optic Connection

### Cable Type:

---

Category 3, 4, 5 or 5e UTP Cable for 10Base-T  
62.5/125µm Multi-Mode Fiber Optic Cable for 10Base-FL

### Distance:

---

100 meter max. for UTP cable  
2,000 meter max. for Multi-Mode fiber optic cable

### Protocol:

---

Baseband

### Standards:

---

IEEE 802.3 10Base-T and 10Base-FL Ethernet

### Connection Switch:

---

2-Position; 10Base-T switch on RJ-45 side for either Hub or Workstation (W/S) connection

### LEDs:

---

LMON, COL, XMT, POWER, RCV, JAB, LINK

### Temperature:

---

0° to 55°C (Standard Operating)

### Humidity:

---

10 to 90% (Non-condensing)

### Dimensions:

---

4.2"(L) x 2.2"(H) x 0.8"(D)

### Power Adapter:

---

9V DC Input, 1A

### EMI:

---

FCC Class A



908 Canada Court  
City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880  
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.  
Specifications subject to change without notice.

# Xtend-T/FL (SM)

## 10Base-T/10Base-FL Converter (Single Mode)

---

PART NUMBER	DESCRIPTION
ETP-20108-SM	10Base-T/FL Single Mode Converter

## Specifications

---

### Interface:

---

RJ-45 Jack for 10Base-T connection  
ST Connector for 10Base-FL Single Mode Fiber Optic Connection

### Cable Type:

---

Category 3, 4, 5 or 5e UTP Cable for 10Base-T  
62.5/125µm Single Mode Fiber Optic Cable for 10Base-FL

### Distance:

---

100 meter max. for UTP cable  
15,000 meter max. for Single Mode fiber optic cable

### Protocol:

---

Baseband

### Standards:

---

IEEE 802.3 10Base-T and 10Base-FL Ethernet

### Connection Switch:

---

2-Position; 10Base-T switch on RJ-45 side for either Hub or Workstation (W/S) connection

### LEDs:

---

LMON, COL, XMT, POWER, RCV, JAB, LINK

### Temperature:

---

0° to 55°C (Standard Operating)

### Humidity:

---

10 to 90% (Non-condensing)

### Dimensions:

---

4.2"(L) x 2.2"(H) x 0.8"(D)

### Power Adapter:

---

9V DC Input, 1A

### EMI:

---

FCC Class A



908 Canada Court  
City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880  
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.  
Specifications subject to change without notice.